DATASHEET PORTABLE METHANE ANALYZER



CH₄/H₂O Portable Methane Analyzer (PMA)

PMA Specifications:

| Measurement Technology | Cavity Enhanced Absorption Spectroscopy |
|---------------------------------------|--|
| Species / Precision | CH_4 : < 10ppb (1 σ , 1s) |
| | $H_2O: < 200ppm (1\sigma, 1s)$ |
| Species / Measurement Range | CH ₄ : 0 – 10,000 ppm |
| | H ₂ O: 0 – 30,000ppm |
| Data Rate | 3 Hz |
| Sample Flow Rate (flow response time) | 3 SLPM (~ 3Hz, 1/e) |
| Ambient Operating Temperature Range | 0 - 50 °C |
| Ambient Humidity Range | 0-95% RH, non-condensing |
| Gas Sample Connectors | QDC (quick disconnect) |
| Network Access | Built in Wi-Fi card, Ethernet (RJ-45) |
| Geospatial Location | GPS on-chip |
| Other Interfaces | 2xUSB-3 / HDMI |
| Dimensions | 9" x 6" x 3.5" |
| Weight | ~ 5 lbs |
| Power Input | 16 - 24 VDC, 5 A |
| Power Consumption | 15 W (with battery fully charged) |
| Battery Powered (Li-Ion) | ~ 5 hrs per full charge (actual time is ambient |
| | temperature dependent) |
| Internal Data Storage | 30 GB eMMC |
| Calibration | Yearly |
| Consumables | Inlet filter (change frequency is site specific) |
| Warranty | 1 yr |